myprojectorlamps.com

The most trusted, dependable name in projector lamp sales.

http://www.myprojectorlamps.com

http://www.myprojectorlamps.ca

http://www.myprojectorlamps.eu

The following projector manual has not been modified or altered in any way.

SHARP®

XV-Z3100U

ENGLISH

FRANÇAIS

ESPAÑOL

PORTUGUÊS

PROJECTOR
PROJECTEUR
PROYECTOR
PROJETOR

OPERATION MANUAL
MODE D'EMPLOI
MANUAL DE MANEJO
MANUAL DE OPERAÇÃO





Before using the projector, please read this operation manual carefully.

Introduction

IMPORTANT

- For your assistance in reporting the loss or theft of your Projector, please record the Serial Number located on the bottom of the projector and retain this information.
- Before recycling the packaging, please ensure that you have checked the contents of the carton thoroughly against the list of "Supplied accessories" on page **10**.

Model No.: XV-Z3100U

Serial No.:

WARNING: High brightness light source. Do not stare into the beam of light, or view directly. Be especially careful that children do not stare directly into the beam of light.

WARNING: To reduce the risk of fire or electric shock, do not expose this product to rain or moisture.

See bottom of projector.

CAUTION

RISK OF ELECTRIC SHOCK. DO NOT REMOVE SCREWS EXCEPT SPECIFIED USER SERVICE SCREW.

CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER.
NO USER-SERVICEABLE PARTS EXCEPT LAMP UNIT.
REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.

The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk or electric shock to persons.

The exclamation point within a triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the product.

WARNING: FCC Regulations state that any unauthorized changes or modifications to this equipment not expressly approved by the manufacturer could void the user's authority to operate this equipment.

U.S.A. ONLY

WARNING:

The cooling fan in this projector continues to run for about 90 seconds after the projector enters standby mode. During normal operation, when putting the projector into standby mode always use the STANDBY/ON button on the projector or the STANDBY button on the remote control. Ensure the cooling fan has stopped before disconnecting the power cord.
DURING NORMAL OPERATION, NEVER TURN THE PROJECTOR OFF BY DISCONNECTING THE POWER CORD. FAILURE TO OBSERVE THIS WILL RESULT IN PREMATURE LAMP FAILURE.

INFORMATION

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the operation manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

U.S.A. ONLY

Declaration of conformity

SHARP PROJECTOR, MODEL XV-Z3100U
This device complies with Part 15 of the FCC rules. Operation is subject to the following conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Responsible Party:

SHARP ELECTRONICS CORPORATION
Sharp Plaza, Mahwah, New Jersey 07430-2135
TEL: 1-800-BE-SHARP (1-800-237-4277)

U.S.A. ONLY

PRODUCT DISPOSAL

This projector utilizes tin-lead solder, and a pressurized lamp containing a small amount of mercury. Disposal of these materials may be regulated due to environmental considerations. For disposal or recycling information, please contact your local authorities or, if you are located in the United States of America, the Electronic Industries Alliance: www.eiae.org .

Caution Concerning Lamp Replacement

See “Replacing the Lamp” on page **56**.

This SHARP projector uses a DLP® chip. This very sophisticated panel contains 921,600 pixels (micromirrors). As with any high technology electronic equipment such as large screen TVs, video systems and video cameras, there are certain acceptable tolerances that the equipment must conform to.
This unit has some inactive pixels within acceptable tolerances which may result in inactive dots on the picture screen. This will not affect the picture quality or the life expectancy of the unit.

How to Read this Operation Manual

■ The specifications are slightly different, depending on the model. However, you can connect and operate all models in the same manner.

- In this operation manual, the illustration and the screen display are simplified for explanation, and may differ slightly from the actual display.



Info .....Indicates safeguards for using the projector.

Note.....Indicates additional information for setting up and operating the projector.

For Future Reference

Maintenance ➡ P. 51

Troubleshooting ➡ PP. 62 and 63

Index ➡ P. 66

Contents

Preparing

Introduction

How to Read this Operation Manual 3
Contents 4
IMPORTANT SAFEGUARDS 6
Accessories 10
Part Names and Functions 11
Inserting the Batteries 14
Usable Range 15

Quick Start

Quick Start 16

Setup

Setting up the Projector 18
Setting up the Projector 18
Standard Setup (Front Projection) 18
Ceiling-mount Setup 18
Projection (PRJ) Mode 19
Picture (Screen) Size and Projection Distance 20

Connections

Samples of Cables for Connection 22
Connecting to Video Equipment 23
Connecting to a Computer 26
Controlling the Projector by a Computer 27

Using

Basic Operation

Turning the Projector On/Off 28
Connecting the Power Cord 28
Turning the Projector on 28
Turning the Power off (Putting the Projector into Standby Mode) 29
Image Projection 29
Switching the Input Mode 29
Adjusting the Projected Image 30
Correcting Trapezoidal Distortion 32
Resize Mode 36

Useful Features

Operating with the Remote Control 38
Selecting the Picture Mode 38
Switching the Iris Setting 38
Freezing a Moving Image 38
Menu Items 39
Using the Menu Screen 41
Menu Selections (Adjustments) 41
Picture Adjustment (“Picture” menu) .. 43
Selecting the Picture Mode 43
Adjusting the Image 43
Adjusting the Color Temperature 44
Adjusting the Colors 44
Progressive 44
Reducing Image Noise (DNR) 45
Switching the Iris Setting 45
Lamp Setting 45
Computer Image Adjustment (“Fine Sync” menu) 46
Adjusting the Computer Image 46
Special Modes Setting 46
Auto Sync (Auto Sync Adjustment) 46
Checking the Input Signal 46
Using the “Options” Menu 47
Adjusting the Overscan 47
Adjusting the Vertical Size of the Display (Subtitle Setting) 47
Setting the On-screen Display 48
Setting the Video System 48
Signal Type Setting 48
Selecting the HDMI Setting 48
Selecting the Background Image 48
Auto Power Off Function 49
Checking the Lamp Life Status 49
Reversing/Inverting Projected Images 49
Selecting the Transmission Speed (RS-232C) 50
Reducing the Power Consumption When the Power Is in Standby Mode 50
Fan Mode Setting 50
Returning to the Default Settings 50
Selecting the On-screen Display Language 50

Reference

Appendix

Maintenance 51
Cleaning and Replacing the Dust Filters 52
Maintenance Indicators 54
Regarding the Lamp 56
- Lamp 56
- Caution Concerning the Lamp 56
- Replacing the Lamp 56
- Removing and Installing the Lamp Unit 57
- Resetting the Lamp Timer 58

Connecting Pin Assignments 59
RS-232C Specifications and Command Settings 60
Computer Compatibility Chart 61
Troubleshooting 62
Service Information (For the U.S.) 63
Specifications 64
Dimensions 65
Index 66
CONSUMER LIMITED WARRANTY (VALID IN USA ONLY) 67
LIMITED WARRANTY (VALID IN CANADA ONLY) 68

IMPORTANT SAFEGUARDS

CAUTION: Please read all of these instructions before you operate this product and save these instructions for later use.

Electrical energy can perform many useful functions. This product has been engineered and manufactured to assure your personal safety. BUT IMPROPER USE CAN RESULT IN POTENTIAL ELECTRICAL SHOCK OR FIRE HAZARDS. In order not to defeat the safeguards incorporated in this product, observe the following basic rules for its installation, use and servicing.

1. **Read Instructions**
   All the safety and operating instructions should be read before the product is operated.
2. **Retain Instructions**
   The safety and operating instructions should be retained for future reference.
3. **Heed Warnings**
   All warnings on the product and in the operating instructions should be adhered to.
4. **Follow Instructions**
   All operating and use instructions should be followed.
5. **Cleaning**
   Unplug this product from the wall outlet before cleaning. Do not use liquid cleaners or aerosol cleaners. Use a damp cloth for cleaning.
6. **Attachments**
   Do not use attachments not recommended by the product manufacturer as they may cause hazards.
7. **Water and Moisture**
   Do not use this product near water–for example, near a bath tub, wash bowl, kitchen sink, or laundry tub; in a wet basement; or near a swimming pool; and the like.
8. **Accessories**
   Do not place this product on an unstable cart, stand, tripod, bracket, or table. The product may fall, causing serious injury to a child or adult, and serious damage to the product. Use only with a cart, stand, tripod, bracket, or table recommended by the manufacturer, or sold with the product. Any mounting of the product should follow the manufacturer's instructions, and should use a mounting accessory recommended by the manufacturer.
9. **Transportation**
   A product and cart combination should be moved with care. Quick stops, excessive force, and uneven surfaces may cause the product and cart combination to overturn.

10. **Ventilation**
    Slots and openings in the cabinet are provided for ventilation to ensure reliable operation of the product and to protect it from overheating, and these openings must not be blocked or covered. The openings should never be blocked by placing the product on a bed, sofa, rug, or other similar surface. This product should not be placed in a built-in installation such as a bookcase or rack unless proper ventilation is provided or the manufacturer's instructions have been adhered to.
11. **Power Sources**
    This product should be operated only from the type of power source indicated on the marking label. If you are not sure of the type of power supply to your home, consult your product dealer or local power company. For products intended to operate from battery power, or other sources, refer to the operating instructions.
12. **Grounding or Polarization**
    This product is provided with one of the following types of plugs. If the plug should fail to fit into the power outlet, please contact your electrician.
    Do not defeat the safety purpose of the plug.
    a. Two-wire type (mains) plug.
    b. Three-wire grounding type (mains) plug with a grounding terminal.
    This plug will only fit into a grounding type power outlet.
13. **Power-Cord Protection**
    Power-supply cords should be routed so that they are not likely to be walked on or pinched by items placed upon or against them, paying particular attention to cords at plugs, convenience receptacles, and the point where they exit from the product.
14. **Lightning**
    For added protection for this product during a lightning storm, or when it is left unattended and unused for long periods of time, unplug it from the wall outlet and disconnect the cable system. This will prevent damage to the product due to lightning and power-line surges.

15. Overloading
Do not overload wall outlets, extension cords, or integral convenience receptacles as this can result in a risk of fire or electric shock.

16. Object and Liquid Entry
Never push objects of any kind into this product through openings as they may touch dangerous voltage points or short-out parts that could result in a fire or electric shock. Never spill liquid of any kind on the product.

17. Servicing
Do not attempt to service this product yourself as opening or removing covers may expose you to dangerous voltage or other hazards. Refer all servicing to qualified service personnel.

18. Damage Requiring Service
Unplug this product from the wall outlet and refer servicing to qualified service personnel under the following conditions:

a. When the power-supply cord or plug is damaged.
b. If liquid has been spilled, or objects have fallen into the product.
c. If the product has been exposed to rain or water.
d. If the product does not operate normally by following the operating instructions. Adjust only those controls that are covered by the operating instructions, as an improper adjustment of other controls may result in damage and will often require extensive work by a qualified technician to restore the product to normal operation.
e. If the product has been dropped or damaged in any way.
f. When the product exhibits a distinct change in performance, this indicates a need for service.

19. Replacement Parts
When replacement parts are required, be sure the service technician has used replacement parts specified by the manufacturer or have the same characteristics as the original part. Unauthorized substitutions may result in fire, electric shock, or other hazards.

20. Safety Check
Upon completion of any service or repairs to this product, ask the service technician to perform safety checks to determine that the product is in proper operating condition.

21. Wall or Ceiling Mounting
This product should be mounted to a wall or ceiling only as recommended by the manufacturer.

22. Heat
This product should be situated away from heat sources such as radiators, heat registers, stoves, or other products (including amplifiers) that produce heat.

- The DLP® logo, the DLP® medallion and BrilliantColor™ are trademarks of Texas Instruments.
- Microsoft® and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries.
- PC/AT is a registered trademark of International Business Machines Corporation in the United States.
- Macintosh® is a registered trademark of Apple Computer, Inc. in the United States and/or other countries.
- HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.
- All other company or product names are trademarks or registered trademarks of their respective companies.
- Some IC chips in this product include confidential and/or trade secret property belonging to Texas Instruments. Therefore you may not copy, modify, adapt, translate, distribute, reverse engineer, reverse assemble or discompile the contents thereof.

Observe the following safeguards when setting up your projector.

Caution concerning the lamp unit

■ Potential hazard of glass particles if lamp ruptures. In case of lamp rupture, contact your nearest Authorized SharpVision Service Center or Dealer for replacement. See "Replacing the Lamp" on page **56**.



Caution concerning the setup of the projector

■ For minimal servicing and to maintain high image quality, SHARP recommends that this projector be installed in an area free from humidity, dust and cigarette smoke. When the projector is subjected to these environments, the vents and lens must be cleaned more often. As long as the projector is regularly cleaned, use in these environments will not reduce the overall operation life of the unit. Internal cleaning should only be performed by an Authorized SharpVision Service Center or Dealer.

Do not set up the projector in places exposed to direct sunlight or bright light.

■ Position the screen so that it is not in direct sunlight or room light. Light falling directly on the screen washes out the colors, making viewing difficult. Close the curtains and dim the lights when setting up the screen in a sunny or bright room.

Caution regarding placing of the projector

■ Place the projector on a level site within the adjustment range (8 degrees) of the adjustment foot.



■ After the projector is purchased, a faint smell from the vent may appear when the power is first turned on. This is normal and is not a malfunction. It will disappear after the projector is used for a while.

When using the projector in high-altitude areas such as mountains (at altitudes of approximately 4,900 feet (1,500 meters) or more)

■ When you use the projector in high-altitude areas with thin air, set "Fan Mode" to "High". Neglecting this can affect the longevity of the optical system.

Warning about placing the projector in a high position

■ When placing the projector in a high position, make certain it is carefully secure to avoid personal injury caused by the projector falling down.

Do not subject the projector to hard impact and/or vibration.

■ Protect the lens so as not to hit or damage the surface of the lens.

Rest your eyes occasionally.

■ Continuously watching the screen for long hours will cause eye strain. Take regular breaks to rest your eyes.

Avoid locations with extremes of temperature.

■ The operating temperature of the projector is from 41°F to 95°F (+5°C to +35°C).

■ The storage temperature of the projector is from –4°F to 140°F (–20°C to +60°C).

Do not block the exhaust and intake vents.

■ Allow at least 11 13/16 inches (30 cm) of space between the exhaust vent and the nearest wall or obstruction.

■ Be sure that the intake vent and the exhaust vent are not obstructed.

■ If the cooling fan becomes obstructed, a protection circuit will automatically put the projector into standby mode to prevent overheat damage. This does not indicate a malfunction. (See pages **54** and **55**.) Remove the projector power cord from the wall outlet and wait at least 10 minutes. Place the projector where the intake and exhaust vents are not blocked, plug the power cord back in and turn on the projector. This will return the projector to the normal operating condition.

- When turning off the projector, the cooling fan runs to decrease the internal temperature for a while. Unplug the power cord after the cooling fan stops. The period the cooling fan runs will vary, depending on the circumstances and the internal temperature.

Caution regarding usage of the projector

- When using the projector, take care not to subject it to hard impact and/or vibration, as this can result in damage. Take extra care with the lens. Before moving the projector, make certain you unplug the power cord from the wall outlet, and disconnect any other cables connected to it.
- Do not carry the projector by holding the lens.
- When storing the projector, ensure you attach the lens cap. (See page **11**).
- Do not expose the projector to direct sunlight or place next to heat sources. Doing so may affect the cabinet color or cause deformation of the plastic cover.

Other connected equipment

- When connecting a computer or other audio-visual equipment to the projector, make the connections AFTER unplugging the power cord of the projector from the AC outlet and turning off the equipment to be connected.
- Please read the operation manuals of the projector and the equipment to be connected for instructions on how to make the connections.

Using the projector in other countries

- The power supply voltage and the shape of the plug may vary depending on the region or country you are using the projector in. When using the projector overseas, make sure you use an appropriate power cord for the country you are in.

Temperature monitor function

- If the projector starts to overheat due to setup problems or blockage of the air vents, "" and "TEMP." will illuminate in the lower left corner of the picture. If the temperature continues to rise, the lamp will turn off, the temperature warning indicator on the projector will blink, and after a 90-second cooling-off period the projector will enter standby mode. Refer to "Maintenance Indicators" on page **54** for details.

Info

- The cooling fan regulates the internal temperature, and its performance is automatically controlled. The sound of the fan may change during projector operation due to changes in the fan speed. This does not indicate malfunction.
- Do not unplug the power cord during projection or cooling fan operation. This can cause damage due to rise in internal temperature, as the cooling fan also stops.

Accessories

Supplied accessories

Remote control
RRMCGA543WJSA

Two R-03 batteries
(“AAA” size, UM/SUM-4,
HP-16 or similar)

Lens cap (attached)
CCAPHA024WJSA



Power cord
for U.S. and
Canada, etc.
(6′ (1.8 m))
QACCDA007WJPZ

- Operation manual

Optional accessories

■ Lamp unit	AN-XR10L2
■ DIN-D-sub RS-232C adaptor (5 $^{57}/_{64}$″ (15 cm))	AN-A1RS
■ 3 RCA to 15-pin D-sub cable (10′ (3.0 m))	AN-C3CP2

Note

- Some of the optional accessories may not be available depending on the region. Please check with your nearest Authorized SharpVision Service Center or Dealer.

Part Names and Functions

Numbers in ▬ refer to the main pages in this operation manual where the topic is explained.

Projector

Top View

Power indicator **28, 54**

28, 54 Lamp indicator

STANDBY/ON button **28**
For turning the power on and putting the projector into standby mode.

54 Temperature warning indicator

29 INPUT buttons (▲/▼)
For switching input mode 1, 2, 3, 4, 5 or 6.

ENTER button **41**
For setting items selected or adjusted on the menu.

RESIZE button **36**
For switching the screen size.

41 MENU button
For displaying adjustment and setting screens.

41 Adjustment buttons (▲/▼/◀/▶)
For selecting menu items.

Front View

51 Intake vent

Focus ring **30**
For adjusting the focus.

30 Zoom ring
For enlarging/ reducing the picture.

HEIGHT ADJUST lever **30**

15 Remote control sensor (front)

Push both sides of the lens cap to attach or remove.

Numbers in ▬ refer to the main pages in this operation manual where the topic is explained.

Rear View



Terminals



Terminal	Description	Page
①	INPUT 1, 2 terminal Connecting video equipment with component output terminal (DVD player, DTV decoder, DVD recorder with hard disc, etc.).	23
②	INPUT 3 terminal Connecting video equipment with S-video output terminal (VCR, DVD player, etc.).	24
③	INPUT 4 terminal Connecting video equipment without S-video output terminal.	24
④	INPUT 5 terminal ■ Connecting video equipment with component output terminal (DVD player, DTV decoder, DVD recorder with hard disc, etc.).	25
	■ Connecting the computer.	26
⑤	INPUT 6 terminal Connecting video equipment with HDMI output terminal.	25
⑥	RS-232C terminal Connecting the computer to control the projector.	27
⑦	TRIGGER terminal When the projector is turned on, a control signal (DC 12V) outputs from this terminal. If an electric screen or other compatible device is connected, it can be turned on when the projector is turned on.	—

Numbers in ▬ refer to the main pages in this operation manual where the topic is explained.



28 ON button
For turning the power on.

29 INPUT 1, 2, 3, 4, 5 and 6 buttons
For switching to the respective input modes.

41 MENU button
For displaying adjustment and setting screens.

41 Adjustment buttons (▲/▼/◀/▶)
- For selecting menu items.
- For adjusting the Keystone Correction when in the Keystone Correction mode.

41 ENTER button
For setting items selected or adjusted on the menu.

36 RESIZE button
For switching the picture size (STRETCH, SIDE BAR, etc.).

38 PICTURE MODE button
For selecting the appropriate picture.

38 IRIS button
For switching “HIGH BRIGHTNESS MODE”, “MEDIUM MODE” and “HIGH CONTRAST MODE”.

29 STANDBY button
For putting the projector into the standby mode.

32 KEYSTONE button
For entering the Keystone Correction mode.

41 RETURN button
For returning to the previous menu screen during menu operations.

46 AUTO SYNC button
For automatically adjusting images when connected to a computer.

48 RGB/COMP. button
For switching to the respective input signal type.

38 FREEZE button
For freezing images.

Backlight button
For lighting all buttons on the remote control.

Using the Kensington Lock on the projector
- This projector has a Kensington Security Standard connector for use with a Kensington MicroSaver Security System. Refer to the information that came with the system for instructions on how to use it to secure the projector.

Inserting the Batteries

1 **Press the ▲ mark on the cover and slide it in the direction of the arrow.**



2 **Insert the batteries.**

- Insert the batteries making sure the polarities correctly match the ⊕ and ⊖ marks inside the battery compartment.



3 **Attach the cover and slide it until it clicks into place.**



Incorrect use of the batteries may cause them to leak or explode. Please follow the precautions below.

⚠ Caution

- Danger of explosion if battery is incorrectly replaced.
  Replace only with the same or equivalent type.
- Insert the batteries making sure the polarities correctly match the ⊕ and ⊖ marks inside the battery compartment.
- Batteries of different types have different properties, therefore do not mix batteries of different types.
- Do not mix new and old batteries.
  This may shorten the life of new batteries or may cause old batteries to leak.
- Remove the batteries from the remote control once they have run out, as leaving them in can cause them to leak.
  Battery fluid from leaked batteries is harmful to skin, therefore ensure you wipe them first and then remove them using a cloth.

- The batteries included with this projector may run down in a short period, depending on how they are kept. Be sure to replace them as soon as possible with new batteries.
- Remove the batteries from the remote control if you will not be using the remote control for a long time.
- Comply with the rules (ordinance) of each local government when disposing of worn-out batteries.

Usable Range

The remote control can be used to control the projector within the ranges shown in the illustration.



Note

- The signal from the remote control can be reflected off a screen for easy operation. However, the effective distance of the signal may differ depending on the screen material.

When using the remote control

- Ensure that you do not drop it or expose it to moisture or high temperature.
- The remote control may malfunction under a fluorescent lamp. In this case, move the projector away from the fluorescent lamp.

Quick Start

This section shows the basic operation (projector connecting with the video equipment).
For details, see the page described below for each step.

Setup and Projection

In this section, connection of the projector and the video equipment is explained using one example.





1. Place the projector facing a wall or a screen ➔P. 18

2. Connect the projector to the video equipment and plug the power cord into the AC socket of the projector ➔PP. 22–28



3. Remove the lens cap and turn the projector on ➔P. 28



On the projector

STANDBY/ON

On the remote control

ON

4. Turn the video equipment on and start playback

5. Select the INPUT mode

➡P. 29

Select the “INPUT 4” using the INPUT buttons on the projector or the INPUT 4 button on the remote control.

On the projector



On the remote control

On-screen display

- When pressing the INPUT buttons on the projector, input mode switches in the following order: INPUT1↔INPUT2↔INPUT3↔INPUT4↔INPUT5↔INPUT6
- Pressing the INPUT buttons on the remote control also allows you to switch the input mode.

6. Adjust the focus, image size, and projector angle

➡PP. 30, 31

1. Adjust the focus by turning the focus ring.



2. Adjust the projection image size by turning the zoom ring.



3. Adjust the projector angle using the HEIGHT ADJUST lever.



7. Correct trapezoidal distortion (GEOMETRIC ADJUSTMENT)

➡PP. 32–35

1. Press KEYSTONE on the remote control.
2. Press ▲/▼/◀/▶ on the remote control to set the upper-left position of the projected image.
3. Press ENTER on the remote control to set the position.
4. Follow steps 2 and 3 to also set the upper-right, lower-right, and lower-left positions of the projected image.
   - When you confirm the lower left position, the screen adjustments will be set and setup will end.

8. Turn the Power off

➡P. 29

Press the STANDBY/ON button on the projector or the STANDBY button on the remote control, and then press the button again while the confirmation message is displayed to put the projector into standby mode.

On the projector

On the remote control

On-screen Display



- Unplug the power cord from the AC outlet after the cooling fan stops.

Setting up the Projector

For optimal image quality, position the projector perpendicular to the screen with the projector's feet flat and level. Doing so will eliminate the need for Keystone correction and provide the best image quality.

Standard Setup (Front Projection)

■ Place the projector at the required distance from the screen according to the desired picture size. (See page **20**.)



Example of standard setup

Side View



Note

- Refer to page **20** for additional information concerning "Picture (Screen) Size and Projection Distance".

Ceiling-mount Setup

■ It is recommended that you use the optional Sharp ceiling-mount bracket for this installation. Before mounting the projector, contact your nearest Authorized SharpVision Service Center or Dealer to obtain the recommended ceiling-mount bracket (sold separately).
- AN-XRCM30 ceiling-mount bracket (for U.S.A.).
- AN-60KT ceiling-mount bracket, its AN-TK201 and AN-TK202 extension tubes (for countries other than the U.S.A.).

■ Invert the image by setting "Ceiling + Front" in "PRJ Mode". See page **49** for use of this function.



Projection (PRJ) Mode

The projector can use any of the 4 projection modes shown in the diagram below. Select the mode most appropriate for the projection setting in use. (You can set the PRJ Mode in “Options2” menu. See page **49**.)

■ Table mounted, front projection



Menu item → “Front”

■ Ceiling mounted, front projection



Menu item → “Ceiling + Front”

■ Table mounted, rear projection (with a translucent screen)



Menu item → “Rear”

■ Ceiling mounted, rear projection (with a translucent screen)



Menu item → “Ceiling + Rear”

Indication of the Projection Image Size and Projection Distance

Refer to page **20** for additional information concerning “Picture (Screen) Size and Projection Distance”.

Example: When using a wide screen (16:9)



Picture (Screen) Size and Projection Distance

The projection screen size varies according to the distance from the lens of the projector to the screen. Install the projector so that projected images are projected onto the screen at the optimum size by referring to the table below. Use the values in the table as a reference when installing the projector.

When using a wide screen (16:9) and projecting 16:9 image

Picture (Screen) size			Projection distance [L]		Distance from the lens center to the bottom of the image [H]
Diag. [χ]	Width	Height	Minimum [L1]	Maximum [L2]	
300″ (762 cm)	261″ (664 cm)	147″ (374 cm)	29′ 9″ (9.1 m)	34′ 5″ (10.5 m)	21 1/32″ (53 cm)
270″ (686 cm)	235″ (598 cm)	132″ (336 cm)	26′ 9″ (8.2 m)	30′11″ (9.4 m)	18 15/16″ (48 cm)
250″ (635 cm)	218″ (553 cm)	123″ (311 cm)	24′ 9″ (7.5 m)	28′ 8″ (8.7 m)	17 17/32″ (45 cm)
200″ (508 cm)	174″ (443 cm)	98″ (249 cm)	19′10″ (6.0 m)	22′11″ (7.0 m)	14 1/64″ (36 cm)
150″ (381 cm)	131″ (332 cm)	74″ (187 cm)	14′10″ (4.5 m)	17′ 2″ (5.2 m)	10 33/64″ (27 cm)
100″ (254 cm)	87″ (221 cm)	49″ (125 cm)	9′11″ (3.0 m)	11′ 6″ (3.5 m)	7 1/64″ (18 cm)
80″ (203 cm)	70″ (177 cm)	39″ (100 cm)	7′11″ (2.4 m)	9′ 2″ (2.8 m)	5 39/64″ (14 cm)
70″ (178 cm)	61″ (155 cm)	34″ (87 cm)	6′11″ (2.1 m)	8′ 0″ (2.4 m)	4 29/32″ (12 cm)
60″ (152 cm)	52″ (133 cm)	29″ (75 cm)	5′11″ (1.8 m)	6′11″ (2.1 m)	4 13/64″ (11 cm)
40″ (102 cm)	35″ (89 cm)	20″ (50 cm)	4′ 0″ (1.2 m)	4′ 7″ (1.4 m)	2 51/64″ (7 cm)

χ: Picture (Screen) size (diag.) (in/cm)
L: Projection distance (ft/m)
L1: Minimum projection distance (ft/m)
L2: Maximum projection distance (ft/m)
H: Distance from the lens center to the bottom of the image (in/cm)

The formula for picture size and projection distance

[Feet/inches]	**[m/cm]**
L1 (ft) = 0.03019χ / 0.3048	L1 (m) = 0.03019χ
L2 (ft) = 0.03493χ / 0.3048	L2 (m) = 0.03493χ
H (in) = 0.17808χ / 2.54	H (cm) = 0.17808χ

When using a normal screen (4:3) and projecting 4:3 image (SIDE BAR Mode)

Picture (Screen) size			Projection distance [L]		Distance from the lens center to the bottom of the image [H]
Diag. [χ]	Width	Height	Minimum [L1]	Maximum [L2]	
300″ (762 cm)	240″ (610 cm)	180″ (457 cm)	36′ 4″ (11.1 m)	42′ 1″ (12.8 m)	25 47/64″ (65 cm)
270″ (686 cm)	216″ (549 cm)	162″ (411 cm)	32′ 9″ (10.0 m)	37′ 10″ (11.5 m)	23 11/64″ (59 cm)
250″ (635 cm)	200″ (508 cm)	150″ (381 cm)	30′ 4″ (9.2 m)	35′ 1″ (10.7 m)	21 29/64″ (54 cm)
200″ (508 cm)	160″ (406 cm)	120″ (305 cm)	24′ 3″ (7.4 m)	28′ 1″ (8.6 m)	17 5/32″ (44 cm)
150″ (381 cm)	120″ (305 cm)	90″ (229 cm)	18′ 2″ (5.5 m)	21′ 0″ (6.4 m)	12 7/8″ (33 cm)
100″ (254 cm)	80″ (203 cm)	60″ (152 cm)	12′ 1″ (3.7 m)	14′ 0″ (4.3 m)	8 37/64″ (22 cm)
80″ (203 cm)	64″ (163 cm)	48″ (122 cm)	9′ 8″ (3.0 m)	11′ 3″ (3.4 m)	6 55/64″ (17 cm)
70″ (178 cm)	56″ (142 cm)	42″ (107 cm)	8′ 6″ (2.6 m)	9′ 10″ (3.0 m)	6″ (15 cm)
60″ (152 cm)	48″ (122 cm)	36″ (91 cm)	7′ 3″ (2.2 m)	8′ 5″ (2.6 m)	5 9/64″ (13 cm)
40″ (102 cm)	32″ (81 cm)	24″ (61 cm)	4′ 10″ (1.5 m)	5′ 7″ (1.7 m)	3 7/16″ (9 cm)

χ: Picture (Screen) size (diag.) (in/cm)
L: Projection distance (ft/m)
L1: Minimum projection distance (ft/m)
L2: Maximum projection distance (ft/m)
H: Distance from the lens center to the bottom of the image (in/cm)

The formula for picture size and projection distance

[Feet/inches]	**[m/cm]**
L1 (ft) = 0.03694χ / 0.3048	L1 (m) = 0.03694χ
L2 (ft) = 0.04275χ / 0.3048	L2 (m) = 0.04275χ
H (in) = 0.21794χ / 2.54	H (cm) = 0.21794χ

When using a normal screen (4:3) and projecting 16:9 image

Picture (Screen) size			Projection distance [L]		Distance from the lens center to the bottom of the image [H]
Diag. [χ]	Width	Height	Minimum [L1]	Maximum [L2]	
300″ (762 cm)	240″ (610 cm)	180″ (457 cm)	27′ 3″ (8.3 m)	31′ 7″ (9.6 m)	19 5/16″ (49 cm)
270″ (686 cm)	216″ (549 cm)	162″ (411 cm)	24′ 7″ (7.5 m)	28′ 5″ (8.7 m)	17 3/8″ (44 cm)
250″ (635 cm)	200″ (508 cm)	150″ (381 cm)	22′ 9″ (6.9 m)	26′ 4″ (8.0 m)	16 3/32″ (41 cm)
200″ (508 cm)	160″ (406 cm)	120″ (305 cm)	18′ 2″ (5.5 m)	21′ 0″ (6.4 m)	12 7/8″ (33 cm)
150″ (381 cm)	120″ (305 cm)	90″ (229 cm)	13′ 8″ (4.2 m)	15′ 9″ (4.8 m)	9 21/32″ (25 cm)
100″ (254 cm)	80″ (203 cm)	60″ (152 cm)	9′ 1″ (2.8 m)	10′ 6″ (3.2 m)	6 7/16″ (16 cm)
80″ (203 cm)	64″ (163 cm)	48″ (122 cm)	7′ 3″ (2.2 m)	8′ 5″ (2.6 m)	5 9/64″ (13 cm)
70″ (178 cm)	56″ (142 cm)	42″ (107 cm)	6′ 4″ (1.9 m)	7′ 4″ (2.2 m)	4 1/2″ (11 cm)
60″ (152 cm)	48″ (122 cm)	36″ (91 cm)	5′ 5″ (1.7 m)	6′ 4″ (1.9 m)	3 55/64″ (10 cm)
40″ (102 cm)	32″ (81 cm)	24″ (61 cm)	3′ 8″ (1.1 m)	4′ 2″ (1.3 m)	2 37/64″ (7 cm)

χ: Picture (Screen) size (diag.) (in/cm)
L: Projection distance (ft/m)
L1: Minimum projection distance (ft/m)
L2: Maximum projection distance (ft/m)
H: Distance from the lens center to the bottom of the image (in/cm)

The formula for picture size and projection distance

[Feet/inches]
L1 (ft) = 0.02771χ / 0.3048
L2 (ft) = 0.03206χ / 0.3048
H (in) = 0.16346χ / 2.54

[m/cm]
L1 (m) = 0.02771χ
L2 (m) = 0.03206χ
H (cm) = 0.16346χ

Note

- Allow a margin of error in the values in the diagrams.

Samples of Cables for Connection

- For more details of connection and cables, refer to the operation manual of the connecting equipment.
- You may need other cables or connectors not listed below.

Equipment	Input Signal	Cable	Terminal on the projector
Audio-visual equipment	HDMI video	HDMI cable (commercially available)	INPUT6
	Compo-nent video	Component cable (commercially available)	INPUT1, 2
	Compo-nent video	3 RCA to 15-pin D-sub cable (optional accessory: AN-C3CP2)	INPUT5
	S-video	S-video cable (commercially available)	INPUT3
	Video	Video cable (commercially available)	INPUT4
Camera/ video game	Compo-nent video	Cables for a camera or a video game	INPUT1, 2
	Compo-nent video	Cables for a camera or a video game 3 RCA to 15-pin D-sub cable (optional accessory: AN-C3CP2) RCA adaptor plug (commercially available)	INPUT5
	S-video	Cables for a camera or a video game	INPUT3
	Video	Cables for a camera or a video game	INPUT4
Computer	RGB video	RGB cable (commercially available)	INPUT5

Connecting to Video Equipment

Before connecting, ensure that the power cord of the projector is unplugged from the AC outlet and turn off the devices to be connected. After making all connections, turn on the projector first and then the other devices.

When connecting the component video equipment to the component input terminal on the projector (INPUT1 or INPUT2)



Connecting to Video Equipment (Continued)

When connecting to equipment with S-video output terminal (INPUT3)



When connecting to equipment with video output terminal (INPUT4)



When connecting the component video equipment to the computer-RGB/ component input terminal on the projector (INPUT5)



When connecting to equipment with HDMI output teminal (INPUT6)

HDMI is a new specialized interface capable of delivering a video and audio signal to the terminal using just one cable. Since this projector does not support an audio signal by itself, use an amplifier or other audio device.
For video connection, use a cable that conforms to HDMI standards. Using cables that do not conform to HDMI standards may result in a malfunction.



Note

- HDMI (High Definition Multimedia Interface) is a digital AV interface that can deliver a high-definition video signal, multi-channel audio signal, and bi-directional control signal all in just one cable.
- Because it is compatible with the HDCP (High-bandwidth Digital Content Protection) system, the digital video signal does not degrade when transmitted, and a high-quality image with a simple connection can be enjoyed.
- When a DVI to HDMI conversion cable is connected to the HDMI terminal, a proper picture may not be displayable.

Connecting to a Computer

When connecting a computer, ensure that it is the last device to be turned on after all the connections are made.

Ensure that you have read the operation manuals of the devices to be connected before making connections.



Note

- See page **61** "Computer Compatibility Chart" for a list of computer signals compatible with the projector. Use with computer signals other than those listed may cause some of the functions to not work.
- A Macintosh adaptor may be required for use with some Macintosh computers. Contact your nearest Macintosh Dealer.
- **Depending on the computer you are using, an image may not be projected unless the computer's external output port is switched on. (e.g. Press "Fn" and "F5" keys simultaneously when using a SHARP notebook computer).** Refer to the specific instructions in your computer's operation manual to enable your computer's external output port.

Controlling the Projector by a Computer

When the RS-232C terminal on the projector is connected to a computer with a DIN-D-sub RS-232C adaptor (optional accessory: AN-A1RS) and an RS-232C serial control cable (cross type, commercially available), the computer can be used to control the projector and check the status of the projector. See page **60** for detail.

When connecting to a computer using an RS-232C serial control cable and a DIN-D-sub RS-232C adaptor



Note

- The RS-232C function may not operate if your computer terminal is not correctly set up. Refer to the operation manual of the computer for details.
- See page **60** for connection of an RS-232C serial control cable.

Info

- Do not connect the RS-232C cable to a port other than the RS-232C terminal on the computer. This may damage your computer or projector.
- Do not connect or disconnect an RS-232C serial control cable to or from the computer while it is on. This may damage your computer.

Turning the Projector On/Off

Connecting the Power Cord

Plug the supplied power cord into the AC socket on the rear of the projector. Then plug into AC outlet.





Turning the Projector on

Note that the connections to external equipment and power outlet should be done before performing the operations written below. (See pages **23** to **28**.)

Remove the lens cap and press ⏻ STANDBY/ON on the projector or ⏻ ON on the remote control.

Note

- **About the Lamp Indicator**
  The lamp indicator illuminates to indicate the status of the lamp.
  Green: The lamp is on.
  Blinking in green: The lamp is warming up or shutting down.
  Red:The lamp is shut down abnormally or the lamp should be replaced.
- When switching on the projector, a slight flickering of the image may be experienced within the first minute after the lamp has been illuminated. This is normal operation as the lamp's control circuitry is stabilising the lamp output characteristics. It should not be regarded as faulty operation.
- If the projector is put into standby mode and immediately turned on again, the lamp may take some time to start projection.

Info

- English is the factory default language. If you want to change the on-screen display to another language, change the language according to the procedure on page **50**.





Turning the Power off (Putting the Projector into Standby Mode)

1 **Press ⏻STANDBY/ON on the projector or ⏻STANDBY on the remote control, then press that button again while the confirmation message is displayed, to put the projector into standby mode.**

2 **Unplug the power cord from the AC outlet after the cooling fan stops.**
- The power indicator on the projector blinks in green while cooling.
- The power indicator changes to red when the projector finishes cooling.

Info
- Do not unplug the power cord during projection or cooling fan operation. This can cause damage due to rise in internal temperature, as the cooling fan also stops.



On-screen Display (confirmation message)



Image Projection

Switching the Input Mode

Select the appropriate input mode for the connected equipment.

Press the appropriate INPUT button on the remote control to select the desired input mode.



- When pressing INPUT (▲/▼) on the projector, input mode switches in the following order:

INPUT1 ⟷ INPUT2 ⟷ INPUT3
↕ ↕
INPUT6 ⟷ INPUT5 ⟷ INPUT4

Adjusting the Projected Image

1 Adjusting the Focus

You can adjust the focus with the focus ring on the projector.

Rotate the focus ring to adjust the focus while watching the projected image.



2 Adjusting the Picture Size

You can adjust the picture size using the zoom ring on the projector.

Rotate the zoom ring to enlarge or shrink the picture size.

3 Adjusting the Height

The height of the projector can be adjusted using the adjustment feet at the front and rear of the projector.

When the screen is above the projector, the projection image can be made higher by adjusting the projector.



1 **Lift the projector to adjust its height while lifting the HEIGHT ADJUST lever.**

2 **Remove your hands from the HEIGHT ADJUST lever of the projector after its height has been finely adjusted.**

- The angle of projection is adjustable up to 8 degrees from the surface on which the projector is placed.



3 Use the rear adjustment foot to make the projector level.

- The projector is adjustable ±1 degree from the standard position.



Note

- When adjusting the height of the projector, trapezoidal distortion occurs. Follow the procedures in Keystone Correction to correct the distortion. (See page **32**.)

Info

- Do not apply too much pressure on the projector when the front adjustment foot comes out.
- When lowering the projector, be careful not to get your fingers caught in the area between the adjustment foot and the projector.
- Hold the projector firmly while lifting or carrying.
- Do not hold by the lens area.

Correcting Trapezoidal Distortion

When the image is projected either from the top or from the bottom towards the screen at an angle, the image becomes distorted trapezoidally. The function for correcting trapezoidal distortion is called Keystone Correction.

There are the two types of the Keystone Correction.

1) **The "GEOMETRIC ADJUSTMENT" method corrects trapezoidal distortion by specifying 4 marks on the screen.**
2) **The "H & V KEYSTONE" method features corrections to 2 axes (horizontal and vertical) based on numerical values.**



Selecting the Type of Correction

Select the Keystone correction method.

Press KEYSTONE on the remote control.

- "GEOMETRIC ADJUSTMENT" will be displayed.
- Each time KEYSTONE is pressed, the display toggles as follows:

GEOMETRIC ADJUSTMENT → H & V KEYSTONE → The display disappears. → GEOMETRIC ADJUSTMENT

GEOMETRIC ADJUSTMENT	For correcting an image by designating the corner of the projected image. (See page **34**.)
H & V KEYSTONE	For correcting an image by designating the horizontal or vertical axes. (See page **35**.)

Note

- When corrections are made with Keystone correction, the changes are saved even if the power cord is unplugged.
- Since Keystone correction digitally corrects the signal, resolution may slightly decrease when it is used. Moiré patterns and line distortions may also be visible in detailed images. However, this is not a malfunction.
- If you cannot correct trapezoidal distortion with Keystone correction, change the placement position of the projector.
- Straight lines and the edges of the displayed image may appear jagged, when adjusting the Keystone setting.
- Also read "About Copyrights" on page **37**.

GEOMETRIC ADJUSTMENT

Info

- When adjusting a 4:3-aspect-ratio input signal to a 4:3-aspect-ratio screen, correct the trapezoidal distortion by setting “RESIZE” to “STRETCH” (16:9).

1 **Press KEYSTONE on the remote control repeatedly until “GEOMETRIC ADJUSTMENT” is displayed.**

2 **Adjust the focus, size, and projection angle so that the screen edges line up into the blue area.**

- Line up the screen edges into the blue area as closely as possible.

3 **Press ▲, ▼, ◄ or ► to move the position for the upper left of the image.**

- Adjust the screen until the displayed red arrows line up in the upper left.

4 **Press ENTER to set the position.**

- The arrow in the upper right turns red.

5 **Repeat the same procedure with the positions for the upper right, lower right and lower left of the image.**

- When you press RETURN at this point, you will return to the previous screen.
- If you press RETURN before adjusting the upper left corner, the Reset Confirmation screen displays.
- **When you confirm the lower left position, the screen adjustments will be set and the “GEOMETRIC ADJUSTMENT” mode will end.**

Note

- The placement of the screen and the projector may result in the image aspect ratio becoming slightly distorted.
- Try “H&V KEYSTONE” when “GEOMETRIC ADJUSTMENT” does not fully correct trapezoidal distortion.

▼ On-screen display





H & V KEYSTONE

1 **Project the image and adjust the focus, image size, and projection angle.**

2 **Press KEYSTONE on the remote control repeatedly until "H & V KEYSTONE" is displayed.**

- When the "GEOMETRIC ADJUSTMENT" mode has been used to adjust the image, a confirmation screen displays before the "H & V KEYSTONE" screen, asking if you want to reset the adjustments or not. Then select RESET.

3 **Press ▲ or ▼ on the remote control to align the left and right sides of the projected image.**

4 **Press ◄ or ► on the remote control to align the upper and lower sides of the projected image.**

5 **Press KEYSTONE or ENTER on the remote control and the "H&V KEYSTONE" mode ends.**

Note

- If adjustments are made using both "H KEYSTONE" and "V KEYSTONE" at the same time, the image aspect ratio may become slightly distorted.
- When adjusting "H KEYSTONE" and "V KEYSTONE" at the same time, the values of adjustable angles for each setting become smaller.
- The adjustable value of the "V KEYSTONE" becomes extremely small when "H KEYSTONE" is made to be the maximum value.

▼ On-screen display

Vertical Keystone Correction (Adjustment with ▲ / ▼)



Horizontal Keystone Correction (Adjustment with ◄ / ►)



Resize Mode

This function allows you to modify or customize the resize mode to enhance the input image. Depending on the input signal, you can choose “STRETCH”, “SIDE BAR”, “CINEMA ZOOM” or “DOT BY DOT (Computer input only)” image.

Press RESIZE on the projector or RESIZE on the remote control.



VIDEO

• “STRETCH” is fixed when 540P, 720P or 1080I signals are entered.

Input Signal		Output screen image		
DVD / Video	Image type	STRETCH	SIDE BAR	CINEMA ZOOM
480I, 480P, 576I, 576P, NTSC, PAL, SECAM	4:3 aspect ratio			
	Letter box			
	Squeezed			
	16:9 aspect ratio			
540P, 720P, 1080I	16:9 aspect ratio		—	—

: Cutout area on which images cannot be projected.

Computer

Input Signal		Output screen image			
Computer	Image type	STRETCH	SIDE BAR	CINEMA ZOOM	DOT BY DOT
VGA, SVGA	4:3 aspect ratio				
XGA (1024×768)	4:3 aspect ratio				
1280×720	16:9 aspect ratio		—	—	—

: Cutout area on which images cannot be projected.

Note

- You can select “CINEMA ZOOM” when with a “VGA/SVGA” signal with a vertical frequency 60 Hz and less. However, when a “VGA/SVGA” signal with a vertical frequency of more than 60 Hz is used, “CINEMA ZOOM” is not available.

About Copyrights

- When using the RESIZE function to select an image size with a different aspect ratio to a TV program or video image, the image will look different from its original appearance. Keep this in mind while choosing an image size.
- The use of the Resize, Keystone Correction, Subtitle, or Overscan function to compress or stretch the image for commercial purposes/public displays in a café, hotel, etc. may be an infringement of copyright protected by law for copyright holders. Please use caution.
- While watching non-widescreen images (4:3), if you use the RESIZE function to fill the screen or use the Overscan function to change the aspect ratio of a fixed-ratio input signal, parts of the outer edge of the image will be cut off or distorted. To watch original images as the producers intended, set RESIZE to “SIDE BAR” and Overscan to its default setting.

Selecting the Picture Mode

You can select the appropriate picture mode to best match the projected image you are watching.

Press PICTURE MODE.

- When pressing PICTURE MODE, the picture mode changes in the following order:

Standard → Natural → Dynamic → Movie1 → Movie2 → Memory → Standard

Note

- See page **43** for details on the picture mode.

Switching the Iris Setting

This function controls the quantity of the projected light and the contrast of the image.

Press IRIS.

- Each time the button is pressed while the display is on, the mode is switched in the following order:

HIGH BRIGHTNESS MODE → MEDIUM MODE → HIGH CONTRAST MODE → HIGH BRIGHTNESS MODE

Note

- For details on Iris, see page **45**.

Freezing a Moving Image

1 **Press FREEZE.**

- The projected image is frozen.

2 **Press FREEZE again to return to the moving image from the currently connected device.**



Menu Items

The following shows the items that can be set in the projector.
The selectable items vary depending on the selected input, input signals, or adjustment values. Items that cannot be selected will be greyed out.

"Picture" menu

PAGE 1



PAGE 2



"C.M.S."



*1 When a video signal, S-video signal, or component 480I/576I signal is input and the Progressive mode is set to "3D Progressive" or "Film Mode", the C.M.S. function cannot be used.

*2 Item that cannot be set when inputting an RGB signal through INPUT 5 or INPUT 6.



Menu Items (Continued)

"Fine Sync" menu



- The "Fine Sync" menu is not available for INPUT 3 or INPUT 4.



"Options1" menu



*1 Item that can be set when using INPUT 3 or INPUT 4.
*2 Item that can be set when using IINPUT 5 or INPUT 6.



"Options2" menu





Using the Menu Screen





Menu Selections (Adjustments)

Example: Adjusting "Bright".

• This operation can also be performed by using the buttons on the projector.

1 **Press MENU.**

• The "Picture" menu screen for the selected input mode is displayed.

2 **Press ▶ or ◀ to select the menu icon to adjust.**

• The selected icon is highlighted.

Menu icon	Menu screen
	Picture
	Fine Sync
	Options1
	Options2

Note

• The "Fine Sync" menu is not available for INPUT 3 or INPUT 4.

Example: "Picture" screen menu for INPUT 1 mode



3 **Press ▲ or ▼ to select the item to adjust.**

- The selected item is highlighted.



Items to be adjusted



To adjust the projected image while watching it

Press ↵ENTER.

- The selected item (e.g. "Bright") is displayed by itself at the bottom of the screen.
- When pressing ▲ or ▼, the following item ("Color" after "Bright") will be displayed.

The item displayed by itself



Note

- Press ↵ENTER again to return to the previous screen.

4 **Press ◄ or ► to adjust the item selected.**

- The adjustment is stored.



5 **Press ▭MENU.**

- The menu screen will disappear.

Note

- The ▭ MENU button does not function while the projector is operating the "Auto Sync" or "FREEZE" functions.

Picture Adjustment (“Picture” menu)

Menu operation ➜ Page **41**

▶ PAGE 1



▶ PAGE 2



① Selecting the Picture Mode

Selectable items	Description	The default settings of each item when selecting Picture Mode			
		CLR Temp	BrilliantColor™	IRIS	Lamp Setting
Standard	For standard image	7500K	0	High Brightness	Bright
Natural	A balanced color image is obtained.	7500K	0	High Brightness	Bright
Dynamic	A vivid image is obtained.	7500K	2	High Brightness	Bright
Movie1	Makes the black levels of the dark portions of the screen more pronounced and vivid.	6500K	0	High Brightness	Eco + Quiet
Movie2	Reduces glare and creates a subdued tone.	6500K	0	Medium Mode	Eco + Quiet
Memory	Allows you to store your picture adjustment settings. The settings stored effect each input mode.	7500K	0	High Brightness	Bright

- You can set or adjust each item in the “Picture” menu to your preference. Any changes you make are retained in memory.

Note
- You can also press PICTURE MODE on the remote control to select the picture mode. (See page **38**.)
- The default settings are subject to change without notice.

② Adjusting the Image

Adjustment items	◀ button	▶ button
Contrast	For less contrast.	For more contrast.
Bright	For less brightness.	For more brightness.
Color*1	For less color intensity.	For more color intensity.
Tint*1	For making skin tones purplish.	For making skin tones greenish.
Sharp*1	For less sharpness.	For more sharpness.
Red	For weaker red.	For stronger red.
Blue	For weaker blue.	For stronger blue.
BrilliantColor™*2	For making the effect weaker.	For making the effect stronger.

*1 Item that cannot be adjusted in RGB mode.
*2 BrilliantColor™ uses Texas Instruments' BrilliantColor™ technology. As the BrilliantColor™ level is increased, the image becomes brighter while the color reproduction is kept at a high level.

Note
- To reset all adjustment items, select “Reset” and press ENTER. The Picture Mode settings of the selected input return to the default settings.

Menu operation ➔ Page 41

③ Adjusting the Color Temperature

Selectable items	Description
5500K 6500K 7500K 8500K 9300K 10500K	For lower color temperature for warmer, reddish incandescent-like images. ↕ For higher color temperature for cooler, bluish, fluorescent-like images.

Note

- Values on "CLR Temp" are only for general standard purposes.

④ Adjusting the Colors

Select "C.M.S." (Color Management System) in the "Picture" menu and then press ↵ ENTER.

This function adjusts each of the six main colors that comprise the color wheel, altering their "Hue", "Saturation", or "Value".

Selectable items	Description
C.M.S.-Hue	Sets the hue of the main colors.
C.M.S.-Saturation	Sets the saturation of the main colors
C.M.S.-Value	Sets the brightness of the main colors.
Reset	The adjustments of "Hue", "Saturation" and "Value" of all colors are reset to the default setting.

Adjusting "Hue", "Saturation", or "Value".

1 Press ▲ or ▼ to select either "Hue", "Saturation", or "Value" and then press ↵ ENTER.
2 Select the color to be adjusted with ▲ or ▼ and adjust it with ◀ or ▶.

Example of adjusting the "Hue"

Main colors	◀ button	▶ button
R (Red)	Closer to magenta	Closer to yellow
Y (Yellow)	Closer to red	Closer to green
G (Green)	Closer to yellow	Closer to cyan
C (Cyan)	Closer to green	Closer to blue
B (Blue)	Closer to cyan	Closer to magenta
M (Magenta)	Closer to blue	Closer to red

- When "Saturation" is selected, the selected color becomes
  ◀: lighter. ▶: thicker.
- When "Value" is selected, the selected color becomes
  ◀: darker. ▶: brighter.
- To reset the adjustment values of each color to the default settings, select "Reset" and press ↵ ENTER.

Info

- When a video signal, S-video signal, or component 480I/576I signal is input, set "Progressive" mode to "2D Progressive" and then adjust the colors.

⑤ Progressive

Selectable items	Description
2D Progressive	Useful to display fast-moving images such as sports.
3D Progressive	Useful to display relatively slow-moving images such as drama and documentary more clearly.
Film Mode	Reproduces the image of film source* clearly. Displays the optimized image of film transformed with three-two pull down (NTSC and PAL60Hz) or two-two pull down (PAL50Hz and SECAM) enhancement to progressive mode images.

* The film source is a digital video recording with the original encoded as is at 24 frames/second. The projector can convert this film source to progressive video at 60 frames/second with NTSC and PAL60Hz or at 50 frames/second with PAL50Hz and SECAM to play back a high-definition image.

Note

- In NTSC or PAL60Hz, even if the 3D Progressive mode has been set, the three-two pull down enhancement will be enabled automatically when the film source has been entered.
- When the image is blurred or noisy, switch to the optimal mode.
- When using progressive inputs, inputs are directly displayed so that 2D Progressive, 3D Progressive and Film Mode cannot be selected.

Info

- The settings can be made either when INPUT3 or INPUT4 are selected or when INPUT1, 2, INPUT5, or INPUT6 are selected and the input signal is 480I or 576I.

⑥ Reducing Image Noise (DNR)

Video digital noise reduction (DNR) provides high quality images with minimal dot crawl and cross color noise.

Selectable items	Description
OFF	DNR does not function.
Level 1-3	Sets the DNR level for viewing a clearer picture.

Note

Set "DNR" to "OFF" in the following cases:
- When the image is blurry.
- When the contours and colors of moving images drag.
- When TV broadcasts with weak signals are projected.

⑦ Switching the Iris Setting

This function controls the quantity of the projected light and the contrast of the image.

Selectable items	Description
High Brightness	High brightness is given priority over high contrast.
Medium Mode	Intermediate mode between high contrast and high brightness.
High Contrast	High contrast is given priority over high brightness.

Note

- You can also use ⓢ IRIS on the remote control to change the Iris. (See page **38**.)

⑧ Lamp Setting

Selectable items	Brightness	Fan sound	Power consumption (When using AC 100V)	Lamp Life
Bright	100%	Normal	303W	Approx. 2,000 hours
Eco + Quiet	Approx. 76%	Low	234W	Approx. 3,000 hours

Note

- When "Lamp Setting" is set to "Eco+Quiet", the power consumption will decrease and the lamp life will extend. (Projection brightness decreases approximately 24%.)

Computer Image Adjustment (“Fine Sync” menu)

Menu operation ➜ Page **41**



① Adjusting the Computer Image

Use the Fine Sync function in case of irregularities such as vertical stripes or flickering in portions of the screen.

Selectable items	Description
Clock	Adjusts vertical noise.
Phase	Adjusts horizontal noise (similar to tracking on your VCR).
H-Pos	Centers the on-screen image by moving it to the left or right.
V-Pos	Centers the on-screen image by moving it up or down.

Note

- You can automatically adjust the computer image by setting “Auto Sync” in the “Fine Sync” menu to “On” or pressing AUTO SYNC on the remote control.
- “Clock”, “Phase”, “H-Pos” and “V-Pos” cannot be adjusted when INPUT 6 is selected.
- The adjustable area of each item may be changed according to the input signal.
- To reset all adjustment items, select “Reset” and press ENTER.

② Special Modes Setting

Ordinarily, the type of input signal is detected and the correct resolution mode is automatically selected. However, for some signals, the optimal resolution mode in “Special Modes” in the “Fine Sync” menu may need to be selected to match the computer display mode.

Note

- Avoid displaying computer patterns which repeat every other line (horizontal stripes). (Flickering may occur, making the image hard to see.)
- Information on the currently selected input signal can be confirmed in item ④.

③ Auto Sync (Auto Sync Adjustment)

Selectable items	Description
On	Auto Sync adjustment will occur when the projector is turned on or when the input signals are switched, when connected to a computer.
Off	Auto Sync adjustment is not automatically performed.

Note

- Auto Sync adjustment is also performed by pressing AUTO SYNC on the remote control.
- The Auto Sync adjustment may take some time to complete, depending on the image of the computer connected to the projector.
- When the optimum image cannot be achieved with Auto Sync adjustment, use manual adjustments.

④ Checking the Input Signal

This function allows you to check the current input signal information.

Using the “Options” Menu

Menu operation ➜ Page **41**



Settings on the Options 1 menu

① Adjusting the Overscan

This function allows you to adjust the Overscan area ratio (display area ratio).

Orientation	◀ button	▶ button
Overscan H (Horizontal)	Reduces the image. (The display area ratio becomes larger.)	Enlarges the image. (The display area ratio becomes smaller.)
Overscan V (Vertical)		

Note

- This function can only be adjusted when a video, S-video, or Component signal is input.
- If the display area ratio is set too large, noise may appear at the screen edges. If this happens, set the display area ratio to a smaller value.
- When “Resize” is set to “CINEMA ZOOM”, depending on the input signal, “Overscan V” may not be adjustable.
- Also read “About Copyrights” on page **37**.

② Adjusting the Vertical Size of the Display (Subtitle Setting)

With this function, you can adjust the vertical size of the display to allow for subtitles.

◀ button	The image is compressed by adjusting the vertical size of the display.
▶ button	The image is enlarged by adjusting the vertical size of the display.

Note

- When changing the screen with the Subtitle setting, not only the bottom of the screen rises, but also the upper part is changed to a certain point.
- The Subtitle setting can be adjusted more effectively with the Overscan function.
- The Subtitle setting only works when “Resize” is set to “CINEMA ZOOM”.
- The adjustment area changes according to the input signal.

Menu operation ➜ Page 41

③ Setting the On-screen Display

Selectable items	Description
On	All On-screen Displays are displayed.
Off	INPUT/FREEZE/AUTO SYNC/RESIZE/ PICTURE MODE/IRIS are not displayed.

④ Setting the Video System

This function can only be set in INPUT 3 or INPUT 4.

The video input system mode is factory preset to “Auto”;however, a clear picture from the connected audio-visual equipment may not be received, depending on the video signal difference. In that case, switch the video signal.

Selectable items	Description
PAL	When connected to PAL video equipment.
SECAM	When connected to SECAM video equipment.
NTSC4.43	When reproducing NTSC signals in PAL video equipment.
NTSC3.58	When connected to NTSC video equipment.

⑤ Signal Type Setting

This function allows you to select the input signal type (RGB or Component) for INPUT 5 or INPUT 6.

Selectable items	Description
Auto	Automatically selects the appropriate input signal between RGB and Component.
RGB	Set when RGB signals are received.
Component	Set when component signals are received.

Note

- You can also select “Signal Type” using RGB/COMP. on the remote control (INPUT 5 or INPUT 6).

⑥ Selecting the HDMI Setting

When there is an HDMI-capable device connected to INPUT 6, an optimum picture may not be displayed if the device’s output signal type and the projector’s input signal type do not match. If this should occur, switch the HDMI Setting.

Selectable items	Description
Standard	When the black levels of the image show banding or appear faded, select the option that results in the best picture quality. (In most circumstances, “Standard” should be selected.)
Enhanced	

Note

- The HDMI Setting can be selected only when INPUT 6 is selected.

⑦ Selecting the Background Image

Selectable items	Description
Blue	Blue screen
None	— (Black screen)

⑧ Auto Power Off Function

Selectable items	Description
On	When no input signal is detected for more than 15 minutes, the projector will automatically enter standby mode.
Off	The Auto Power Off function will be disabled.

Note

- When the Auto Power Off function is set to "On", 5 minutes before the projector enters standby mode, the message "Enter STANDBY mode in X min." will appear on the screen to indicate the remaining minutes.

⑨ Checking the Lamp Life Status

You can confirm the cumulative lamp usage time and the remaining lamp life (percentage).

Lamp usage condition	Remaining lamp life	
"Life"	100%	5%
Operated exclusively with Lamp Setting set to "Eco + Quiet"	Approx. 3,000 hours	Approx. 150 hours
Operated exclusively with Lamp Setting set to "Bright"	Approx. 2,000 hours	Approx. 100 hours

Note

- It is recommended that the lamp be changed when the remaining lamp life becomes 5%.
- The lamp life may vary depending on the usage condition.



Settings on the Options 2 menu

① Reversing/Inverting Projected Images

Selectable items	Description
Front	Normal image (Projected from the front of the screen)
Ceiling + Front	Inverted image (Projected from the front of the screen with an inverted projector)
Rear	Reversed image (Projected from the rear of the screen or with a mirror)
Ceiling + Rear	Reversed and inverted image (Projected with a mirror)

See page **19** for details of Projection (PRJ) Mode.

Menu operation ➜ Page 41

② Selecting the Transmission Speed (RS-232C)

Make sure that both the projector and computer are set for the same baud rate.

Selectable items	Description
9600bps	Transmission speed is slow.
115200bps	Transmission speed is rapid.

③ Reducing the Power Consumption When the Power Is in Standby Mode

When “STANDBY Mode” has been set to “Standard”, the RS-232C function is activated and power is consumed even in standby mode. It is recommended that “STANDBY Mode” be set to “Eco” when it is not being used. This reduces power consumption when the projector is in standby mode.

Selectable items	Description
Standard	The RS-232C function is activated even if the projector is in standby mode.
Eco	The RS-232C function is switched off when the projector is in standby mode.

Note

- When you want to control the projector using the RS-232C function, set to “Standard”.

④ Fan Mode Setting

This function changes the fan rotation speed.

Selectable items	Description
Normal	Suitable for normal environments.
High	Select this when using the projector at altitudes of approximately 4,900 feet (1,500 meters) or more.

When “Fan Mode” is set to “High”, the fan rotation speeds up, and the fan noise becomes louder.

⑤ Returning to the Default Settings

Use “All Reset” to initialize all the adjustments you have made to the default settings.

Note

The following items cannot be initialized.

- “Fine Sync” menu
  – Special Modes
- “Options1” menu
  – Lamp Timer (Life)
  – Language

⑥ Selecting the On-screen Display Language

The projector can switch the on-screen display language among 11 languages.

English	Svenska
Deutsch	Português
Español	汉语
Nederlands	한국어
Français	日本語
Italiano	

Maintenance

Cleaning the projector

- Ensure that you have unplugged the power cord before cleaning the projector.
- The cabinet as well as the operation panel is made of plastic. Avoid using benzene or thinner, as these can damage the finish on the cabinet.
- Do not use volatile agents such as insecticides on the projector.
  Do not attach rubber or plastic items to the projector for long periods.
  The effects of some of the agents in the plastic may cause damage to the quality or finish of the projector.
- Wipe off dirt gently with a soft flannel cloth.
- When the dirt is hard to remove, soak a cloth in a mild detergent diluted with water, wring the cloth well and then wipe the projector.
  Strong cleaning detergents may discolor, warp or damage the coating on the projector. Make sure to test on a small, inconspicuous area on the projector before use.



Cleaning the lens

- Use a commercially available blower or lens cleaning paper (for glasses and camera lenses) for cleaning the lens. Do not use any liquid type cleaning agents, as they may wear off the coating film on the surface of the lens.
- As the surface of the lens can easily get damaged, be careful not to scrape or hit the lens.



Cleaning the exhaust and intake vents

- Use a vacuum cleaner to clean dust from the exhaust vent and the intake vent.



Info

- If you want to clean the air vents during projector operation, ensure you press STANDBY/ON on the projector or STANDBY on the remote control and put the projector into standby mode. After the cooling fan has stopped, clean the vents.

Cleaning and Replacing the Dust Filters

Cleaning the Dust Filters

Info

- The dust filters should be cleaned every 100 hours of use. Clean the filters more often when the projector is used in a dusty or smoky location.

1 **Press STANDBY/ON on the projector to put the projector into standby mode.**

- Wait until the cooling fan stops.
- Disconnect the power cord and unplug the power cord from the AC socket.



2 **Remove the filter holders.**

- Turn the projector over. To remove the filter holders, press in the tabs while lifting up.



3 **Clean the dust off the dust filters and the holders with a hand broom.**



4 **Replace the filter holders.**

- Align the tabs on the filter holders while replacing them, and then press down on the tabs to lock them in place.



Note

- Be sure the filter holders are securely installed. The power will not turn on unless it is correctly installed.

Replacing the Dust Filters

Info

- If the filters become too dirty to clean effectively, purchase new ones (PFILDA025WJZZ) from your nearest Authorized SharpVision Service Center or Dealer.

After removing the filter holders (see step 2 of "Cleaning the Dust Filters"), remove the dust filters, then replace with new ones.

- Pick the dust filters up with your fingers and lift them out of the filter holders.
- With the reinforcement seal facing down, place the dust filters underneath the tabs on the filter holders.



Maintenance Indicators

- The warning lights (power indicator, lamp indicator and temperature warning indicator) on the projector indicate problems inside the projector.
- If a problem occurs, either the temperature warning indicator or the lamp indicator will illuminate red, and the projector will enter standby mode. After the projector has entered standby mode, follow the procedures given below.

Top View



About the temperature warning indicator

If the temperature inside the projector increases, due to blockage of the air vents, or the setting location, "TEMP." will illuminate in the lower left corner of the picture. If the temperature keeps on rising, the lamp will turn off and the temperature warning indicator will blink, the cooling fan will run, and then the projector will enter standby mode. After "TEMP." appears, ensure you perform the measures described on page **55**.

About the lamp indicator

- When the remaining lamp life becomes 5% or less, (yellow) and "Change The Lamp" will be displayed on the screen. When the percentage becomes 0%, it will change to (red), the lamp will automatically turn off and then the projector will automatically enter standby mode. At this time, the lamp indicator will illuminate in red.
- **If you try to turn on the projector a fourth time without replacing the lamp, the projector will not turn on.**

Indicators on the Projector

Power indicator	Red on	Normal (Standby)
	Green on	Normal (Power on)
	Red blinks	Abnormal (See page **55**.)
	Green blinks	Normal (Cooling)
Lamp indicator	Green on	Normal
	Green blinks	The lamp is warming up or shutting down.
	Red on	The lamp is shut down abnormally or requires to be changed. (See page **55**.)
Temperature warning indicator	Off	Normal
	Red on	The internal temperature is abnormally high. (See page **55**.)

Maintenance indicator			Problem	Cause	Possible Solution
	Normal	Abnormal			
Tempera-ture warning indicator	Off	Red on (Standby)	The internal temperature is abnormally high.	• Blocked air intake	• Relocate the projector to an area with proper ventilation. (See page **8**.)
				• Cooling fan breakdown • Internal circuit failure • Clogged air intake	• Take the projector to your nearest Authorized SharpVision Service Center or Dealer for repair.
Lamp indicator	Green on (Green blinks when the lamp is warming up or turning off.)	Red on	The lamp does not illuminate.	• The lamp is shut down abnormally.	• Disconnect the power cord from the AC outlet, and then connect it again.
			Time to change the lamp.	• Remaining lamp life becomes 5% or less.	• Carefully replace the lamp. (See page **57**.) • Take the projector to your nearest Authorized SharpVision Service Center or Dealer for repair. • Please exercise care when replacing the lamp. • Securely install the cover.
		Red on (Standby)	The lamp does not illuminate.	• Burnt-out lamp • Lamp circuit failure	
Power indicator	Green on/ Red on Green blinks (Cooling)	Red blinks	The power indicator blinks in red when the projector is on.	• The dust filter holder or lamp unit cover is open.	• If the power indicator blinks in red even when the dust filter holders and lamp unit cover are securely installed, contact your nearest Authorized SharpVision Service Center or Dealer for advice.

Info

- If the temperature warning indicator illuminates, and the projector enters standby mode, follow the possible solutions above and then wait until the projector has cooled down completely before plugging in the power cord and turning the power back on. (At least 10 minutes.)
- If the power is turned off for a brief moment due to power outage or some other cause while using the projector, and the power supply recovers immediately after that, the lamp indicator will illuminate in red and the lamp may not be lit. In this case, unplug the power cord from the AC outlet, replace the power cord in the AC outlet and then turn the power on again.
- The cooling fan keeps the internal temperature of the projector constant and this function is controlled automatically. The sound of the cooling fan may change during operation because the fan speed may change and this is not a malfunction.
- Do not unplug the power cord after the projector has entered standby mode and while the cooling fan is running. The cooling fan runs for about 90 seconds.

Regarding the Lamp

Lamp

- It is recommended that the lamp (sold separately) be replaced when the remaining lamp life becomes 5% or less, or when you notice a significant deterioration in the picture and color quality. The lamp life (percentage) can be checked with the on-screen display. (See page **49**.)
- Purchase a replacement lamp of type AN-XR10L2 from your place of purchase, nearest Authorized SharpVision Service Center or Dealer.

IMPORTANT NOTE TO U.S. CUSTOMERS:

The lamp included with this projector is backed by a 90-day parts and labor limited warranty. All service of this projector under warranty, including lamp replacement, must be obtained through an Authorized SharpVision Service Center or Dealer. For the name of the nearest Authorized SharpVision Service Center or Dealer, please call toll-free: 1-888-GO-SHARP (1-888-467-4277).

Hg LAMP CONTAINS MERCURY For State Lamp Disposal Information
www.lamprecycle.org or 1-800-BE-SHARP

U.S.A. ONLY

Caution Concerning the Lamp

- This projector utilizes a pressurized mercury lamp. A loud sound may indicate lamp failure. Lamp failure can be attributed to numerous sources such as: excessive shock, improper cooling, surface scratches or deterioration of the lamp due to a lapse of usage time.
  The period of time up to failure largely varies depending on the individual lamp and/or the condition and the frequency of use. It is important to note that failure can often result in the bulb cracking.
- When the lamp replacement indicator and on-screen display icon are illuminated, it is recommended that the lamp be replaced with a new one immediately, even if the lamp appears to be operating normally.
- Should the lamp break, there is also a possibility that glass particles may spread inside of the projector. In such a case, it is recommended you contact your nearest Authorized SharpVision Service Center or Dealer to assure safe operation.
- Should the lamp break, the glass particles may spread inside the lamp cage or gas contained in the lamp may be vented into the room from the exhaust vent. Because the gas in this lamp includes mercury, ventilate the room well if the lamp breaks and avoid all exposure to the released gas. In case of exposure to the gas, consult a doctor as soon as possible.

Replacing the Lamp

- Do not remove the lamp unit from the projector right after use. The lamp will be very hot and may cause burn or injury.

- **Carefully change the lamp by following the instructions described in this section. * If you wish, you may have the lamp replaced at your nearest Authorized SharpVision Service Center or Dealer.**

* If the new lamp does not light after replacement, take your projector to the nearest Authorized SharpVision Service Center or Dealer for repair.

Removing and Installing the Lamp Unit

Warning!

- The lamp unit becomes very hot while the projector is operating. Do not remove the lamp unit from the projector right after use. The lamp and parts around the lamp will be very hot and may cause burns or injury.

Info

- Make sure that you remove the lamp unit by the handle. Do not touch the glass surface of the lamp unit or the inside of the projector.
- To avoid injury to yourself and damage to the lamp, make sure you carefully follow the steps below.
- Do not loosen other screws except for the lamp unit cover and lamp unit.

Optional accessory



Lamp unit
AN-XR10L2

1 **Press STANDBY/ON on the projector or STANDBY on the remote control to put the projector into standby mode.**

- Wait until the cooling fan stops.



2 **Disconnect the power cord.**

- Unplug the power cord from the AC socket.
- Leave the lamp until it has fully cooled down (about 1 hour).

3 **Remove the lamp unit cover.**

- Turn the projector over. Loosen the user service screw (①) that secures the lamp unit cover. Remove the lamp unit cover (②).



4 **Remove the lamp unit.**

- Loosen the securing screws from the lamp unit. Hold the lamp unit by the handle and pull it in the direction of the arrow. At this time, keep the lamp unit horizontal and do not tilt it.



5 **Insert the new lamp unit.**

- Press the lamp unit firmly into the lamp unit compartment. Fasten the securing screws.



6 **Replace the lamp unit cover.**

- Align the tab on the lamp unit cover (①) and place it while pressing the tab (②) to close it. Then tighten the user service screw (③) to secure the lamp unit cover.



Info

- If the lamp unit and lamp unit cover are not correctly installed, the power will not turn on, even if the power cord is connected to the projector.

Resetting the Lamp Timer

Reset the lamp timer after replacing the lamp.

Info

- Make sure to reset the lamp timer only when replacing the lamp. If you reset the lamp timer and continue to use the same lamp, this may cause the lamp to become damaged or explode.



1 **Connect the power cord.**

- Plug the power cord into the AC socket of the projector.

2 **Reset the lamp timer.**

- While simultaneously holding down MENU, ENTER and ▼ on the projector, press STANDBY/ON on the projector.
- "LAMP 0000H" is displayed, indicating that the lamp timer is reset.



Connecting Pin Assignments

COMPUTER-RGB/COMPONENT INPUT5 Terminal: 15-pin Mini D-sub female connector



COMPUTER-RGB Input	Component Input
1. Video input (red)	1. PR (CR)
2. Video input (green/sync on green)	2. Y
3. Video input (blue)	3. PB (CB)
4. Not connected	4. Not connected
5. Not connected	5. Not connected
6. Earth (red)	6. Earth (PR)
7. Earth (green/sync on green)	7. Earth (Y)
8. Earth (blue)	8. Earth (PB)
9. Not connected	9. Not connected
10. GND	10. Not connected
11. Not connected	11. Not connected
12. Bi-directional data	12. Not connected
13. Horizontal sync signal: TTL level	13. Not connected
14. Vertical sync signal: TTL level	14. Not connected
15. Data clock	15. Not connected

RS-232C Terminal: 9-pin Mini DIN female connector



Pin No.	Signal	Name	I/O	Reference
1.				Not connected
2.	RD	Receive Data	Input	Connected to internal circuit
3.	SD	Send Data	Output	Connected to internal circuit
4.				Not connected
5.	SG	Signal Ground		Connected to internal circuit
6.				Not connected
7.	RS	Request to Send		Connected to CS in internal circuit
8.	CS	Clear to Send		Connected to RS in internal circuit
9.				Not connected

RS-232C Terminal: 9-pin D-sub male connector of the DIN-D-sub RS-232C adaptor (optional accessory: AN-A1RS)



Pin No.	Signal	Name	I/O	Reference
1.				Not connected
2.	RD	Receive Data	Input	Connected to internal circuit
3.	SD	Send Data	Output	Connected to internal circuit
4.				Not connected
5.	SG	Signal Ground		Connected to internal circuit
6.				Not connected
7.	RS	Request to Send		Connected to CS in internal circuit
8.	CS	Clear to Send		Connected to RS in internal circuit
9.				Not connected

RS-232C Cable recommended connection: 9-pin D-sub female connector



Pin No.	Signal	Pin No.	Signal
1.	CD	1.	CD
2.	RD	2.	RD
3.	SD	3.	SD
4.	ER	4.	ER
5.	SG	5.	SG
6.	DR	6.	DR
7.	RS	7.	RS
8.	CS	8.	CS
9.	CI	9.	CI

Note

- Depending on the controlling device used, it may be necessary to connect Pin 4 and Pin 6 on the controlling device (e.g. computer).

Projector Pin No.	Computer Pin No.
4	4
5	5
6	6

Connecting Pin Assignments (Continued)

HDMI Terminal



Pin No.	Name	Pin No.	Name	Pin No.	Name
1.	TMDS Data2+	8.	TMDS Data0 Shield	14.	Reserved
2.	TMDS Data2 Shield	9.	TMDS Data0-	15.	SCL
3.	TMDS Data2-	10.	TMDS Clock+	16.	SDA
4.	TMDS Data1+	11.	TMDS Clock Shield	17.	DDC/CEC Ground
5.	TMDS Data1 Shield	12.	TMDS Clock-	18.	+5V Power
6.	TMDS Data1-	13.	CEC	19.	Hot Plug Detect
7.	TMDS Data0+				

RS-232C Specifications and Command Settings

Computer control

A computer can be used to control the projector by connecting an RS-232C serial control cable (cross type, sold separately) to the projector. (See page 27 for connection.)

Communication conditions

Set the serial port settings of the computer to match that of the table.

Signal format: Conforms to RS-232C standard.
Baud rate: * 9,600 bps/115,200 bps
Data length: 8 bits
Parity bit: None
Stop bit: 1 bit
Flow control: None
*** Set the projector's baud rate to the same rate as used by the computer.**

Basic format

Commands from the computer are sent in the following order: command, parameter, and return code. After the projector processes the command from the computer, it sends a response code to the computer.

Command format

C1	C2	C3	C4	P1	P2	P3	P4	Return code (0DH)

Command 4-digit — Parameter 4-digit

Response code format

Normal response

O	K	Return code (0DH)

Problem response (communication error or incorrect command)

E	R	R	Return code (0DH)

Info

- When controlling the projector using RS-232C commands from a computer, wait for at least 30 seconds after the power has been turned on, and then transmit the commands.
- When more than one code is being sent, send each command only after the response code for the previous command from the projector is verified.

Commands

Example: When turning on the projector, make the following setting.

Computer → Projector

P	O	W	R	_	_	_	1	⏎	→	O	K	⏎

CONTROL CONTENTS	COMMAND				PARAMETER				RETURN
Power Off	P	O	W	R	_	_	_	0	OK or ERR
Power On	P	O	W	R	_	_	_	1	OK or ERR
INPUT 1 (Video1 : Component1)	I	V	E	D	_	_	_	1	OK or ERR
INPUT 2 (Video2 : Component2)	I	V	E	D	_	_	_	2	OK or ERR
INPUT 3 (Video3 : S-Video)	I	V	E	D	_	_	_	3	OK or ERR
INPUT 4 (Video4 : Video)	I	V	E	D	_	_	_	4	OK or ERR
INPUT 5 (RGB1 : RGB/Component)	I	R	G	B	_	_	_	1	OK or ERR
INPUT 6 (RGB2 : RGB/Component)	I	R	G	B	_	_	_	2	OK or ERR

Note

- If an underbar (_) appears in the parameter column, enter a space.

Computer Compatibility Chart

Computer

- Multiple signal support
  Horizontal Frequency: 15-70 kHz,
  Vertical Frequency: 45-85 Hz,
  Pixel Clock: 12-85 MHz
  Sync signal: Compatible with TTL level
- Compatible with sync on green signal
- Expansion System resizing technology

The following is a list of modes that conform to VESA. However, this projector supports other signals that are not VESA standards.

PC/MAC	Resolution		Horizontal Frequency (kHz)	Vertical Frequency (Hz)	VESA Standard	HDMI Support	Display
PC	VGA	640 × 350	27.0	60			Upscale
			31.5	70			
			37.5	85	✔		
		640 × 400	27.0	60			
			31.5	70			
			37.9	85	✔		
		720 × 350	27.0	60			
			31.5	70			
		720 × 400	27.0	60			
			31.5	70			
			37.9	85	✔		
		640 × 480	26.2	50			
			31.5	60	✔	✔	
			34.7	70			
			37.9	72	✔		
			37.5	75	✔		
			43.3	85	✔		
	SVGA	800 × 600	31.4	50			
			35.1	56	✔		
			37.9	60	✔		
			46.6	70			
			48.1	72	✔		
			46.9	75	✔		
			53.7	85	✔		
	XGA	1,024 × 768	40.3	50			Intelligent compression
			48.4	60	✔		
			56.5	70	✔		
			60.0	75	✔		
	—	1,280 × 720	45.0	60			True
		1,280 × 768	47.8	60			Intelligent compression
MAC 13"	VGA	640 × 480	34.9	67			Upscale
MAC 16"	SVGA	800 × 600	37.8	60			
		832 × 624	49.7	75			
MAC 19"	XGA	1,024 × 768	60.2	75			Intelligent compression

Note

- When this projector receives 640 × 350 VESA format VGA signals, “640 × 400” appears on the screen.

DTV

Signal	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	HDMI Support
480I	15.7	60	✓
480P	31.5	60	✓
540P	33.8	60	
576I	15.6	50	✓
576P	31.3	50	✓
720P	37.5	50	✓
720P	45.0	60	✓
1035I	28.1	50	
1035I	33.8	60	
1080I	28.1	50	✓
1080I	33.8	60	✓

Troubleshooting

Problem	Check	Page
 Picure does not appear or projector does not start.	• Projector power cord is not plugged into the wall outlet.	**28**
	• Power to the external connected devices is off.	–
	• The selected input mode is wrong.	**29**
	• Cables incorrectly connected to the projector.	**23–27**
	• Remote control battery has run out.	**14**
	• External output has not been set when connecting notebook computer.	**26**
	• The lamp unit cover is not installed correctly.	**57, 58**
	• The dust filter holders are not installed correctly.	**52, 53**
 No picture appears (or picture is dark).	• Cables incorrectly connected to the projector.	**23–27**
	• “Bright” is set to minimum position.	**43**
	• Depending on the computer you are using, an image may not be projected unless the signal output setting of the computer is switched to the external output. Refer to the computer’s operation manual for how to switch its signal output settings.	–
 Color is faded or poor.	• Image adjustments are incorrectly set. • Make adjustments to “Color”, “Tint” and “BrilliantColor™” in “Picture Mode”.	**43**
	(Video Input only) • Video input system is incorrectly set.	**48**
 Picture is blurred; noise appears.	• Adjust the focus.	**30**
	• The projection distance exceeds the focus range.	**20**
	• There is fog on the lens. If the projector is carried from a cold room into a warm room, or if it is suddenly heated, condensation may form on the surface of the lens and the image will become blurred. Please set up the projector at least one hour before it is to be used. If condensation should form, remove the power cord from the wall outlet and wait for it to clear.	–
	(Computer Input only) • Perform “Fine Sync” Adjustments (“Clock” Adjustment) • Perform “Fine Sync” Adjustments (“Phase” Adjustment) • Noise may appear depending on the computer.	 **46** **46** –
Picture is green on INPUT 5 (Component)/ INPUT 6 (Component).	• Select “Signal Type” in the “Options1” menu and change the input signal type.	**48**
Picture is pink (no green) on INPUT 5 (RGB)/INPUT 6 (RGB).		
An unusual sound is occasionally heard from the cabinet.	• If the picture is normal, the sound is due to cabinet shrinkage caused by room temperature changes. This will not affect operation or performance.	–
Maintenance indicator on the projector illuminates or blinks in red.	• See “Maintenance Indicators”.	**54**

Problem	Check	Page
Picture is too bright and whitish.	• Image adjustments are incorrectly set.	**43**
The black levels of the image show banding or appear faded when INPUT 6 is selected.	• Select the HDMI Setting (“Standard” or “Enhanced”) that results in the best picture quality.	**48**
The cooling fan becomes noisy.	• When temperature inside the projector increases, the cooling fan runs faster.	**8, 9** **51-55**
The lamp does not light up even after the projector turns on.	• The lamp indicator is illuminating in red. Replace the lamp.	**54, 57**
The lamp suddenly turns off during projection.		
The image sometimes flickers.	• Cables incorrectly connected to the projector or the connected equipment works improperly. • If this happens frequently, replace the lamp.	**23-27** **57**
The lamp needs much time to turn on.	• The lamp will eventually need to be changed. While the remaining lamp life draws to a close, replace the lamp.	**57**
Picture is dark.		
The remote control cannot be used.	• Operate the remote control while pointing it at the projector’s remote control sensor. • The remote control may be too far away from the projector. • If direct sunlight or a strong fluorescent light is shining on the projector’s remote control sensor, place the projector where it will not be affected by strong light.	**15**
	• The batteries may be depleted or inserted incorrectly. Make sure the batteries are inserted correctly or insert new ones.	**14**

This unit is equipped with a microprocessor. Its performance could be adversely affected by incorrect operation or interference. If this should happen, unplug the Unit and plug it in again after more than 5 minutes.

Service Information (For the U.S.)

For the location of the nearest Authorized SharpVision Service Center, or to obtain product literature, accessories, supplies or customer assistance, please call 1-800-BE-SHARP (1-800-237-4277) or visit SHARP’s website (http://www.sharpusa.com).

Specifications

Product type	Projector
Model	XV-Z3100U
Video system	NTSC3.58/NTSC4.43/PAL/PAL-M/PAL-N/PAL-60/SECAM/DTV480I/DTV480P/DTV540P/DTV576I/DTV576P/DTV720P/DTV1035I/DTV1080I/DTV1080I-50
Display method	DLP® chip Panel size: 0.62″ Drive method: Digital Light Processing (DLP®) No. of dots: 921,600 dots (1280 [H] × 720 [V])
Lens	1–1.15 × zoom lens, F2.4–2.6, f = 19.0–21.9 mm
Projection lamp	220 W DC lamp
Component input signal (INPUT1/2)	RCA connector Y: 1.0 Vp-p, sync negative, 75 Ω terminated P_B (C_B): 0.7 Vp-p, 75 Ω terminated P_R (C_R): 0.7 Vp-p, 75 Ω terminated
S-video input signal (INPUT 3)	4-pin mini DIN connector Y (luminance signal): 1.0 Vp-p, sync negative, 75 Ω terminated C (chrominance signal): Burst 0.286 Vp-p, 75 Ω terminated
Video input signal (INPUT 4)	RCA connector: VIDEO, composite video, 1.0 Vp-p, sync negative, 75 Ω terminated
Computer RGB/ Component input signal (INPUT 5)	15-pin mini D-sub connector RGB separate/sync on green type analog input: 0–0.7 Vp-p, positive, 75 Ω terminated HORIZONTAL SYNC. SIGNAL: TTL level (positive/negative) VERTICAL SYNC. SIGNAL: Same as above
HDMI input signal (INPUT 6)	HDMI terminal (video signal only)
Horizontal resolution	720 TV lines (DTV720P)
Vertical frequency	45–85 Hz
Horizontal frequency	15–70 kHz
Pixel clock	12–85 MHz
RS-232C terminal	9-pin mini DIN connector
TRIGGER terminal	Power jack: DC 12V output
Rated voltage	AC 100–240 V
Input current	3.1 A
Rated frequency	50/60 Hz
Power consumption	303 W (Lamp Setting "Bright")/ 234 W (Lamp Setting "Eco + Quiet") with AC 100 V 293 W (Lamp Setting "Bright")/ 228 W (Lamp Setting "Eco + Quiet") with AC 240 V
Power consumption (standby)	4 W (AC 100 V) – 5 W (AC 240 V)*1
Heat dissipation	1,140 BTU/hour (Lamp Setting "Bright")/ 1,100 BTU/hour (Lamp Setting "Eco + Quiet") with AC 100 V 880 BTU/hour (Lamp Setting "Bright")/ 860 BTU/hour (Lamp Setting "Eco + Quiet") with AC 240 V
Operating temperature	41°F to 95°F (+5°C to +35°C)
Storage temperature	–4°F to 140°F (–20°C to +60°C)
Cabinet	Plastic
I/R carrier frequency	38 kHz
Dimensions (approx.)	12 13/32″ × 4 19/64″ × 11 1/32″ (315 (W) × 109 (H) × 280 (D) mm) (main body only) 12 13/32″ × 4 47/64″ × 11 37/64″ (315 (W) × 120 (H) × 294 (D) mm) (including adjustment foot and projecting parts)
Weight (approx.)	8.8 lbs. (4.0 kg)
Replacement parts	Remote control, Power cord for U.S. and Canada, etc., Operation manual

*1 When STANDBY Mode is set to "Eco"

As a part of policy of continuous improvement, SHARP reserves the right to make design and specification changes for product improvement without prior notice. The performance specification figures indicated are nominal values of production units. There may be some deviations from these values in individual units.

Dimensions

Units: inches (mm)







Index

AC socket 28
Accessories 10
Adjustment buttons 41
Aspect ratio 36
Auto Power Off 49
Auto Sync
(Auto Sync adjustment) 46
AUTO SYNC button 46

Background 48
Backlight button 13
Blue 43
Bright 43
BrilliantColor™ 43

Checking the Input Signal 46
CINEMA ZOOM 36, 37
Clock 46
CLR Temp (Color Temperature) 44
C.M.S. 44
Color 43
Contrast 43

DOT BY DOT 37
DNR 45
Dust filters 52

ENTER button 41
Exhaust vent 12, 51

Fan Mode 50
Fine Sync 46
Focus ring 30
FREEZE button 38

GEOMETRIC ADJUSTMENT 34

H & V KEYSTONE 35
HDMI Setting 48
H-Pos 46
HEIGHT ADJUST lever 30
Hue 44

INPUT 1 terminal 23
INPUT 1 – 6 modes 29
INPUT 2 terminal 23
INPUT 3 terminal 24
INPUT 4 terminal 24
INPUT 5 terminal 25, 26
INPUT 6 terminal 25
INPUT buttons 29
Intake vent 11, 12, 51
IRIS button 38

Kensington Security
Standard connector 12, 13
KEYSTONE button 32
Keystone Correction 32

Lamp 10, 56
Lamp indicator 54
Lamp Setting 45
Lamp Timer (Life) 49
Lamp unit 57
Language (on-screen display language) 50
Lens cap 11

MENU button 41

ON button 28
Optional accessories 10
OSD Display 48
Overscan 47

Phase 46
Picture Adjustment 43
Picture Mode 38, 43
PICTURE MODE button 38
Picture (Screen) Size and Projection Distance 20
Power cord 28
PRJ Mode 19, 49
Progressive 44

R-03 batteries 14
Rear adjustment foot 31
Red 43
Remote control 13
Remote control sensor 15
Replacing the lamp 56, 57
Resize 36, 37
RESIZE button 36
RETURN button 41
RGB/COMP. button 48
RS-232C Setting 50
RS-232C terminal 27

Saturation 44
Sharp 43
SIDE BAR 36, 37
Special Modes 46
STANDBY button 29
STANDBY/ON button 28, 29
STANDBY Mode 50
STRETCH 36, 37
Subtitle 47
Supplied accessories 10

Temperature warning indicator 54
Tint 43
TRIGGER terminal 12

Value 44
Video System 48
V-Pos 46

Zoom ring 30

CONSUMER LIMITED WARRANTY

SHARP ELECTRONICS CORPORATION warrants to the first consumer purchaser that this Sharp brand product (the "Product"), when shipped in its original container, will be free from defective workmanship and materials, and agrees that it will, at its option, either repair the defect or replace the defective Product or part thereof with a new or remanufactured equivalent at no charge to the purchaser for parts or labor for the period(s) set forth below.

This warranty does not apply to any appearance items of the Product nor to the additional excluded item(s) set forth below nor to any Product the exterior of which has been damaged or defaced, which has been subjected to improper voltage or other misuse, abnormal service or handling, or which has been altered or modified in design or construction.

In order to enforce the rights under this limited warranty, the purchaser should follow the steps set forth below and provide proof of purchase to the servicer.

The limited warranty described herein is in addition to whatever implied warranties may be granted to purchasers by law. ALL IMPLIED WARRANTIES INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE ARE LIMITED TO THE PERIOD(S) FROM THE DATE OF PURCHASE SET FORTH BELOW. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.

Neither the sales personnel of the seller nor any other person is authorized to make any warranties other than those described herein, or to extend the duration of any warranties beyond the time period described herein on behalf of Sharp.

The warranties described herein shall be the sole and exclusive warranties granted by Sharp and shall be the sole and exclusive remedy available to the purchaser. Correction of defects, in the manner and for the period of time described herein, shall constitute complete fulfillment of all liabilities and responsibilities of Sharp to the purchaser with respect to the Product, and shall constitute full satisfaction of all claims, whether based on contract, negligence, strict liability or otherwise. In no event shall Sharp be liable, or in any way responsible, for any damages or defects in the Product which were caused by repairs or attempted repairs performed by anyone other than an authorized servicer. Nor shall Sharp be liable or in any way responsible for any incidental or consequential economic or property damage. Some states do not allow the exclusion of incidental or consequential damages, so the above exclusion may not apply to you.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS. YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

Model Specific Section (In-Home Service)

Your Product Model Number & Description:	XV-Z3100U Projector (Be sure to have this information available when you need service for your Product.)
Warranty Period for this Product:	One (1) year parts and labor from date of purchase except for the Projector Lamp for which the warranty period is ninety (90) days from date of purchase. After the ninety (90) day warranty period on the Projector Lamp, parts and labor for a lamp replacement are the responsibility of the consumer.
Additional Item(s) Excluded from Warranty Coverage (if any):	Cleaning of Optical System and/or replacement of any filter. Labor & materials required to remove and reinstall a suspended projector in installations not accessible with a standard (8' step) ladder or ceilings exceeding 12' in height. Labor & materials required to remove and reinstall a projector in complex systems including, but not limited to, projectors installed in custom enclosures, projectors connected to third party control and automation systems, and realignment of projectors installed in "mirrored" rear projection enclosures.
Where to Obtain Service:	From a Sharp Authorized Servicer located in the United States. To find the location of the nearest Sharp Authorized Servicer, call Sharp toll free at 1-800-BE-SHARP.
What to do to Obtain Service:	Contact your Sharp Authorized Servicer to obtain in-home service for this Product. The Servicer will come to your home and if necessary to remove the Product for repair at the Servicer's facility, the Servicer will reinstall it upon completion of repair. Be sure to have **Proof of Purchase** available.

TO OBTAIN PRODUCT INFORMATION, CALL **1-800-BE-SHARP (1-800-237-4277)** OR VISIT www.sharpusa.com.

VALID IN CANADA ONLY

SHARP®

LIMITED WARRANTY

Consumer Electronics Products

Congratulations on your purchase!

Sharp Electronics of Canada Ltd. (hereinafter called "Sharp") gives the following express warranty to the first consumer purchaser for this Sharp brand product, when shipped in its original container and sold or distributed in Canada by Sharp or by an Authorized Sharp Dealer:

Sharp warrants that this product is free, under normal use and maintenance, from any defects in material and workmanship. If any such defects should be found in this product within the applicable warranty period, Sharp shall, at its option, repair or replace the product as specified herein.

This warranty shall not apply to:

(a) Any defects caused or repairs required as a result of abusive operation, negligence, accident, improper installation or inappropriate use as outlined in the owner's manual.
(b) Any Sharp product tampered with, modified, adjusted or repaired by any party other than Sharp, Sharp's Authorized Service Centres or Sharp's Authorized Servicing Dealers.
(c) Damage caused or repairs required as a result of the use with items not specified or approved by Sharp, including but not limited to head cleaning tapes and chemical cleaning agents.
(d) Any replacement of accessories, glassware, consumable or peripheral items required through normal use of the product including but not limited to earphones, remote controls, AC adapters, batteries, temperature probe, stylus, trays, filters, belts, ribbons, cables and paper.
(e) Any cosmetic damage to the surface or exterior that has been defaced or caused by normal wear and tear.
(f) Any damage caused by external or environmental conditions, including but not limited to transmission line/power line voltage or liquid spillage.
(g) Any product received without appropriate model, serial number and CSA/cUL markings.
(h) Any products used for rental or commercial purposes.
(i) Any installation, setup and/or programming charges.

Should this Sharp product fail to operate during the warranty period, warranty service may be obtained upon delivery of the Sharp product together with proof of purchase and a copy of this LIMITED WARRANTY statement to an Authorized Sharp Service Centre or an Authorized Sharp Servicing Dealer. In home warranty service may be provided at Sharp's discretion on any Sharp television with the screen size of 27" or larger and on any Sharp Over The Range Microwave Oven.

This warranty constitutes the entire express warranty granted by Sharp and no other dealer, service centre or their agent or employee is authorized to extend, enlarge or transfer this warranty on behalf of Sharp. To the extent the law permits, Sharp disclaims any and all liability for direct or indirect damages or losses or for any incidental, special or consequential damages or loss of profits resulting from a defect in material or workmanship relating to the product, including damages for the loss of time or use of this Sharp product or the loss of information. The purchaser will be responsible for any removal, reinstallation, transportation and insurance costs incurred. Correction of defects, in the manner and period of time described herein, constitute complete fulfillment of all obligations and responsibilities of Sharp to the purchaser with respect to the product and shall constitute full satisfaction of all claims, whether based on contract, negligence, strict liability or otherwise.

WARRANTY PERIODS

Projector	1 year (bulb 90 days)

To obtain the name and address of the nearest Authorized Sharp Service Centre or Dealer, please contact:
SHARP ELECTRONICS OF CANADA LTD.

SHARP ELECTRONICS OF CANADA LTD.
335 Britannia Road East
Mississauga, Ontario
L4Z 1W9
(905) 568-7140
Web site: www.sharp.ca

TO BE THE BEST
SHARP
SERVICE
THROUGH CUSTOMER SATISFACTION

SHARP

SHARP CORPORATION

Printed in China
Imprimé en Chine
Impreso en China
Impresso na China
TINS-C776WJZZ
06P11-CH-NG